



受控文件

安装尺寸

SPECIFICATION:

Operating temperature: -25 °C ~ 70 °C  
 Rated loading: AC 12V 50mA  
 Contact resistance: 100mΩ Max  
 Insulation resistance: 100MΩ Min  
 Withstanding voltage: AC 250V (50Hz) /min  
 Operating force: 250±30gf Max  
 Electrical Life: 50000 cycles

电路图



5			黄铜	镀银
4		1PCS	PPA	黑色
3	弹片	1PCS	覆银铜	
2	底座	1PCS	黄铜	镀铜锡
1	接线片	1PCS	PPA	
序列号	名称	数量	材料	备注

General tolerance: ±0.2mm H=5.0±0.2 L=3.85±0.2

NO.	NAME	MATERIAL	QTY.	FINISHING
1	Terminal	Brass	1	Silver plating
2	Case	PA66	1	Black
3	Contact	Phosphor bronze	1	Ag plating
4	Cover	SUS	1	
5	Stem	PA66	1	Black

**深圳市兴烨电子有限公司**  
 Shenzhen XingYe Electronics co., Ltd

TOLERANCE		
X.X	±0.30	X.° ±2°
.XX	±0.20	.X° ±1°
.XXX	±0.10	.XX° ±0.5°
UNITS	mm	

Series Name :			
Product Name :	6*6*5边二脚260G编带		
Part NO:	TSE12062		
SCALE	SHEET	REV.	
1:1	1/1	A1	

APPD: 陈爱光  
 CHED: 施立敏  
 DRAW: 马洪飞