


PCB SOLDER LAND DIMENSIONS



Specifications

Contact Rating	50mA, 12V DC
Contact Resistance	50mA, 12V DC
Insulation Resistance	100mΩ min. 500V DC
Dielectric Strength	250V AC/1minute
Travel	0.13mm
Operating Temp	-30°C~+85°C
Storage Temp	-30°C~+85°C

受控文件



ITEM	PAPT NAMF	TERNO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp	—	—
②	Cover	—	1	Sus	Plating Nickel	—
①	Keystake	—	1	Pa46/Brass	—	—

深圳市兴烨电子有限公司
 Shenzhen XingYe Electronics co., Ltd

Series Name : _____

Product Name : 3*2*0.6贴片120G编带

Part NO: **TSQ22186**

TOLERANCE	SCALE	SHEET	REV.
X.X ±0.30 X.° ±2°	1:1	1/1	A1
.XX ±0.20 X.° ±1°			
.XXX ±0.10 XX.° ±0.5°			
UNITS mm			

APPD: 陈爱光
 CHED: 施立敏
 DRAW: 马洪飞