



REV.	ECN NO.	DESCRIPTION	DRAW	APPD	DATE
A	---				

Pin Number	Signal Name
1	VBUS
2	D-
3	D+
4	ID
5	GND

受控文件

Specification:
 Current rating: 1,5PIN 1.5A Max/2,3,4PIN 1A Max.
 Dielectric withstanding voltage: 30 V(ac) for 1 min.
 Contact resistance: 30 mΩ Max.
 Insulation resistance: 100 MΩ Min.
 Total mating force: 3.57 Kgf Max.
 Total unmating force: 1.02Kgf Min.
 Temperature range: -30°C~80°C



No.	Pare Name	Number	Material	Remarks
3	Shell	1PCS	copper alloy	
2	Contacts	5PCS	copper alloy	t=0.20mm
1	Housing	1PCS	LCP	UL94v-0

深圳市兴烨电子有限公司
 ShenZhen XingYe Electronics co., Ltd

TOLERANCE			
X.X	±0.30	X.°	±2°
.XX	±0.20	.X°	±1°
.XXX	±0.10	.XX°	±0.5°
UNITS		mm	

Series Name :		
Product Description :	MICRO-5P-F焊线式	
Part NO:	MKG26246	
SCALE	SHEET	REV.
1:1	1/1	A1

APPD: 陈爱光
 CHED: 施立敏
 DRAW: 马洪飞