



備注:

1. 材質:
- 1.1 端子: C5191R-EH, T=0.15mm.
 - 1.2 胶芯: LCP+30%GF; 顏色: 黑色
 - 1.3 外壳: SUS 304R-1/2H.T0.30mm
2. 电镀:
- 2.1 端子: 电镀镍底50u"Min. (焊接区域) 锡脚电镀亮锡80u"Min.
 - 2.2 外壳: 电镀镍底50u"Min.
 - 2.3

料号对照表:



品名	品名电镀规格
014101010-037	单排SMT LCP黑色镀金3u"
014109020-046	单排SMT PA46橙色镀金3u"
014106020-047	单排SMT PA46绿色镀金3u"
014102020-085	单排SMT LCP黑色镀金30u"
014102020-062	单排SMT LCP本色镀金3u"

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm



深圳市兴烨电子有限公司
Shenzhen XingYe Electronics Co., Ltd

Series Name :

Product Name :
TYPE-CF-16P板上四脚全贴L7.35

TOLERANCE	
X.X ±0.30	X.° ±2°
.XX ±0.20	.X° ±1°
.XXX ±0.10	.XX° ±0.5°
UNITS	mm

APPD: 陈爱光
CHED: 施立敏
DRAW: 马洪飞

Part NO: UCM27546

SCALE	SHEET	REV.
1:1	1/1	A1