

REV.	ECN NO.	DESCRIPTION	DRAW	APPD.	DATE
A	---				

PIN数	料号	尺寸	
		A	B
2P	TZD24616	3.0	9.6
3P	TZD24617	6.0	12.6
4P	TZD24618	9.0	15.6
5P	TZD24619	12.0	18.6
6P	TZD24620	15.0	21.6
7P	TZD24621	18.0	24.6
8P	TZD24622	21.0	27.6
9P	TZD24623	24.0	30.6
10P	TZD24624	27.0	33.6
11P	TZD24625	30.0	36.6
12P	TZD24626	33.0	39.6



受控文件

- SPECIFICATIONS**
- Current Rating: 3.5A AC, DC
  - Voltage Rating: 250V AC, DC
  - Temperature Range: -25 °C ~ +85 °C
  - Contact Resistance: 20mΩ Max
  - Insulation Resistance: 1000MΩ Min
  - Withstanding Voltage: 1000V AC/minute
  - Material: LCP UL94V-0
- PIN Material: brass.Matte-plated  
Available in 02 through 12 Circuits.

序号	图号	名称	材料	数量	附件
3	③	基座	LCP	1	UL94V-0
2	②	焊片	黄铜	2	镀亚光
1	①	接触件	黄铜	N*	镀亚光

深圳市兴烨电子有限公司  
ShenZhen XingYe Electronics co., Ltd

Series Name :  
30004-43650单排3.0-nP卧贴带扣

Product Description :

Part NO:

TOLERANCE		APPD: 姚人凤 CHED: 施立敏 DRAW: 马洪飞	SCALE: 1:1	SHEET: 1/1	REV: A1
X.X	±0.30				
.XX	±0.20				
.XXX	±0.10				
UNITS	mm				

